

Semi-electric aerial order picker

Specification

Model Number			SEP2-2.7	SEP2-3.3	SEP2-4.0	SEP2-4.5
Max.Platform Height	(H)	mm	2720	3300	4000	4500
Max.Machine Height	(H1)	mm	4020	4900	5400	6100
Ground Clearance	(H2)	mm	30	30	30	30
Lift Rated Capacity		kg	200	200	200	200
Platform Size		mm	600*600	600*640	600*640	600*640
Lifting Motor	(1Xn)	v/kw	12/1.6	12/1.6	12/1.6	12/1.6
Aneroid Battery		V/Ah	12/120	12/120	12/120	12/120
Charger		V/A	12/15	12/15	12/15	12/15
Overall Length	(A)	mm	1300	1300	1320	1320
overall Width	(B)	mm	850	850	850	850
Overall Height	(C)	mm	1760	2040	1830	2000
Overall Net Weight		kg	270	320	380	420



Self-propelled electric aerial order picker

Specification

Model Number			FSEP3-2.7	FSEP3-3.3	FSEP3-4.0	FSEP3-4.5
Max.Platform Height	(H)	mm	2700	3300	4000	4500
Max.Machine Height	(H1)	mm	4120	5000	5400	6000
Ground Clearance	(H1)	mm	40	40	40	40
Lift Rated Capacity		kg	300	300	300	300
Platform Size		mm	600*640	600*640	600*640	600*640
Max. Drive speed(Paltform Stowed)		km/h	4	4	4	4
Max. Drive speed(Paltform Elevated)		km/h	1.6	1.6	1.6	1.6
Min. Turning Radius		mm	1600	1600	1600	1600
Max. climbing capacity		%	15~20	15~20	15~20	15~20
Driving wheel size		mm	Φ230*80	Φ230*80	Φ230*80	Φ230*80
Caster size		in	6	6	6	6
Driving motor		v/kw	2*24/0.4	2*24/0.4	2*24/0.4	2*24/0.4
Lifting Motor		v/kw	24/1.6	24/1.6	24/1.6	24/1.6
Aneroid Battery		V/Ah	2*12/150	2*12/150	2*12/150	2*12/150
Charger		V/A	24/15	24/15	24/15	24/15
Overall Length	(A)	mm	1530	1530	1620	1620
Overall Width	(B)	mm	700	700	700	700
Overall Height	(C)	mm	1830	2130	1840	2000
Overall Net Weight		kg	430	450	660	680

